

Appl. No. 10/647,521

Attorney Docket No. 10541-1832

RECEIVED
CENTRAL FAX CENTER
OCT 15 2007

I. Listing of Claims

1. (Currently Amended) A vehicle temperature control system, comprising:

a housing having an intake opening for air intake and an output opening for output air;

an evaporator core disposed in the housing and in fluid communication with the intake opening;

a heater core disposed in the housing downstream from the evaporator core and in fluid communication with the evaporator core, defining a space between the evaporator core and the heater core, the heater core having a first portion and a second portion, the second portion of the heater core being closer to the output opening than the first portion of the heater core, the heater core having an input face and an output face, the output face being located closer to the evaporator core than the input face; and

a separation wall having a first end and a second end, the first end being attached to the first portion of the heater core and extending therefrom along the length of the heater core in the space between the evaporator core and the heater core towards the output opening.

2. (Original) The system of claim 1 wherein the heater core has an input face and an output face and wherein the separation wall defines a flow channel from the evaporator core to the input face of the heater core.

BRINKS HOFER GILSON & LIONE
PO Box 10395

- 2 -

Appl. No. 10/647,521

Attorney Docket No. 10541-1832

3. (Original) The system of claim 1 wherein the evaporator core and the heater core are in side by side relationship.
4. (Original) The system of claim 1 wherein the evaporator core has an input side and an output side, the input side being adjacent to the intake opening and the output side being adjacent to the separation wall.
5. (Original) The system of claim 4 further comprising of a blower disposed in the housing and upstream from the evaporator core for introducing air into the input side of the evaporator core.
6. (Original) The system of claim 1 wherein the housing is a drain area adjacent to the evaporator core for condensation and a drain hole formed through the housing for condensation drainage.
7. (Original) The system of claim 1 wherein the separation wall isolates a cold air portion and a hot air portion of the space between the evaporator core and the heater core, the cold air portion being adjacent to evaporator core and the hot air portion being adjacent to the heater core.
8. (Previously Presented) The system of claim 7, wherein the separation wall defines a mixing channel for mixing cold air and hot air, the mixing channel being downstream and in fluid communication with the evaporator core and the heater core.



BRINKS
HOFER
GILSON
PO Box 10395
Chicago, IL 60611-5699

- 3 -

Appl. No. 10/647,521

Attorney Docket No. 10541-1832

9. (Cancelled)

10. (Cancelled)

11. (Original) The system of claim 8 wherein the mixing channel is a first mixing channel and the separation wall is a first separation wall.

12. (Original) The system of claim 11, wherein the second portion of the heater core is spaced apart from the housing forming a hot air entrance.

13. (Cancelled)

14. (Cancelled)

15. (Cancelled)

16. (Cancelled)

17. (Cancelled)



BRINKS
HOFER
GILSON
& LIONE
PO Box 10395

- 4 -